

# PROJECTOR 100

## CONSTRUCTION & MINING EQUIPMENT

### Spraying

For spraying of wet mortar, mixed concrete and other wet products.  
Used as a service hose between pump and nozzle in transporting plaster, grout and ready mixed concrete.

### Advantages

- High working pressure.
- Light weight, flexible and easy to handle.
- Abrasion resistant tube.

### Technical description

**Inner tube:** wear resistant NR, black, smooth.

**Reinforcement:** synthetic textile.

**Cover:** wear and weather resistant SBR, black, fabric impression.

**Temperature range:** -30°C to +70°C.

**Electrical properties:** conductive tube,  $R < 2 \cdot 10^6 \Omega/m$ .

**Special properties:** abrasion resistance of tube  $< 70 mm^3$  according to ISO 4649.

### Complementary information

13.3m lengths available on request, min. order is three pieces and by multiple of three.  
Other wall thickness and/or bursting pressure on request.



ID mm	Wall thickness mm	OD mm	Working pressure bar	Bursting pressure bar	Bending radius mm	Weight kg/m	Length m	Notes
<b>25.0</b>	7.0 +0/-1	39.0 ±1.0	40	100	100	0.87	<b>40</b>	
<b>32.0</b>	8.0 +0/-1	48.0 ±1.0	40	100	150	1.24	40	
<b>35.0</b>	6.5 +0/-1	48.0 ±1.0	40	100	180	1.06	<b>40</b>	
<b>38.0</b>	10.0 +0/-1	58.0 ±1.0	40	100	180	1.84	40	
<b>40.0</b>	10.0 +0/-1	60.0 ±1.0	40	100	200	1.92	40	
<b>50.0</b>	7.5 ±0.7	65.0 ±1.5	40	100	370	1.64	40	
<b>50.0</b>	9.0 ±0.7	68.0 ±1.5	40	100	280	2.04	<b>40</b>	
<b>60.0</b>	10.0 ±0.7	80.0 ±1.5	40	100	340	2.72	40	
<b>65.0</b>	10.0 ±0.7	85.0 ±1.5	40	100	380	2.93	<b>40</b>	

Tolerance on length: ±1% (ISO 1307 Standard).

Lengths in bold = stock item. Other lengths = non stock (consult us for minimum quantity of order).

### Branding

