

# CONTI® Fire hose CO<sub>2</sub>

Safety on a very high level

## Application

The CONTI® Fire hose CO<sub>2</sub> provides highest safety and reliability in case of conditions of severity and thus should not be missed on any portable fire extinguisher. Hydrant hoses according to EN 694 can also be delivered.

## Description

- › Black, non-porous and smooth SBR lining
- › Reinforcements: synthetic fibres
- › Black SBR-cover, resistant to ozone, weather, UV and abrasion
- › Working pressure up to 30 bar / 435 psi
- › Temperature range from -30°C up to +80°C / -22°F up to +176°F
- › Electrically conductive,  $R < 10^8 \Omega$
- › Suitable for any portable fire extinguisher usual in the trade

## Technical data

nominal width zoll/inch	inner-Ø mm	wall thickness mm	length m	working pressure		min. burst pressure		min. bending radius aprx. mm	weight aprx. g/m
				bar	psi	bar	psi		
3/8	10	3.0	40	30	435	90	1305	100	170
3/8	10	3.0	80	30	435	90	1305	100	170
1/2	13.2	3.8	40	30	435	90	1305	132	270
1/2	13.2	3.8	80	30	435	90	1305	132	270

Pressure based on room temperature / High pressure and/or temperature lead to reduced component durability

